

METROSPEC

# Outdoor Interactive Kiosk

The Metrospec Outdoor Interactive Kiosk is engineered for durability and high visibility in various outdoor environments. Its robust design ensures reliable performance in harsh weather conditions, making it ideal for public spaces across Australia and New Zealand.



## Key Features



### Brilliant & Durable

Sunlight-readable display with 1500 nits brightness & anti-reflective,



### Durable

Weather-resistant, IP65-rated enclosure, shatter-resistant glass.



### Customisable

Customisable design with single or double-sided configurations. Touchscreen optional.



### Easy Install

Easy installation, time-saving and labor-saving operation and maintenance



## Applications

This kiosk is ideal for deployment in a wide range of public environments, including transit stops, transport interchanges, outdoor shopping centres, tourist information centres, educational campuses, petrol stations, public streetscapes, zoos, and theme parks.

- ✓ Transport Interchanges
- ✓ Educational Campuses
- ✓ Shopping Centres
- ✓ Public Spaces

Contact Us



07 3868 4255

# Weatherproof & Durable Design for Outdoor Use

Engineered for year-round performance, this outdoor kiosk features a rugged, IP65-rated enclosure that protects against rain, dust, heat, and vandalism. Its high-brightness, sunlight-readable LCD and anti-reflective glass ensure clear visibility even in direct sunlight, while its robust construction withstands Australia and New Zealand's most demanding outdoor environments.



## Specifications

Below are the technical specifications for the MetroSpec Outdoor Interactive Kiosk. This information outlines key performance, environmental, and connectivity features to assist with project planning and integration.

Specification	Details
Size	Range of sizes available
Resolution	Customisable
Brightness	1500 nits
Contrast Ratio	4000:1 (typical)
Response Time	8 ms (typical)
Viewing Angle	178° horizontal / 178° vertical
Half-Life	50,000 hours
Active Area	572.67 mm (H) x 1018.08 mm (W)
Power Consumption	205W
Material	Aluminium
Standard Colour	Black (custom colours available)
Dimensions	790 mm (H) x 1800 mm (W) x 207 mm (D)
Weight	80 kg
Front Glass	6.4 mm anti-reflective, UV and shatter-resistant
Floor Plinth	Stainless steel, 790 mm x 150 mm

Specification	Details
Operating Temperature	-20°C to +50°C (optional extension to -40°C with internal environmental control system)
Storage Temperature	-20°C to +60°C
Humidity	10% to 90%
Network	Ethernet, Wi-Fi, 3G/4G
Ports	USB, DVI, VGA, RGB, Composite
Audio	Built-in speakers (optional)
Touchscreen Options	IR or P-CAP
Remote Control	Password-protected
Condensation Protection	Yes
Temperature Protection	Over/under temperature protection
Environmental Control	Intelligent internal environmental control
Remote Control	With AAA batteries (optional)
Quick Start Guide	Included
VGA Cable	Included
Mounting Options	Wall, side, ceiling brackets (optional)